



VINYL SKIRTING KITS

Based on box size lineal footage (LF). Panel quantities change with height variations. Pick the panel column that reflects your average height. Determine average height with several measurements from ground to 1"- 2" overlap on siding. Consult our skirting representative for special quotes.

Box Size (LF) ▼	Panels up to 28" Avg. Ht.	Panels up to 35" Avg. Ht.	Panels up to 46" Avg. Ht.	Trim Kit (165 LF)	Top Back Trim	Top Front Trim	Ground Channel	Weed-Eater Guard	Hex Screws	7" Ground Spikes
14 x 36 (100)	15	19	25	-	10	10	10	10	300	70
12 x 56 (136)	21	26	34	-	13	13	13	13	400	90
14 x 56 (140)	21	27	35	-	13	13	13	13	400	90
16 x 56 (144)	22	27	36	-	14	14	14	14	500	100
32 x 42 (148)	23	28	37	-	14	14	14	14	500	100
28 x 48 (152)	23	29	38	-	14	14	14	14	500	100
28 x 52 (160)	24	30	40	1	-	-	-	15	500	100
28 x 56 (168)	26	32	42	1	1	1	1	16	500	110
28 x 60 (176)	27	33	44	1	1	1	1	16	500	110
16 x 76 (184)	28	35	46	1	2	2	2	17	500	115
18 x 76 (188)	29	36	47	1	3	3	3	18	500	120
28 x 68 (192)	29	36	48	1	3	3	3	18	500	125
32 x 66 (196)	30	37	49	1	3	3	3	18	500	125
28 x 72 (200)	30	38	50	1	4	4	4	19	500	130
28 x 76 (208)	32	39	52	1	4	4	4	19	500	130
32 x 76 (216)	33	41	54	1	5	5	5	20	600	135

Helpful Notes:

*To determine average height, measure from ground to bottom of home siding at each corner and middle of long sides, add up all measurements and divide by total number of measurements, then add 1 inch. (Example: 30 + 34 + 29 + 27 + 32 + 30 = 182 inches, divided by 6 measurements = 30.33 inches, plus 1 inch = 31.33 average height. This will determine how many cuts you can get from a full panels, and how many panels you will need. A full 140" panel will yield (3) 46" cuts, (4) 35" cuts, or (5) 28" cuts.

*Trim Kits Contain (15) Top Back, (15) Top Front, (15) Ground Channel, enough trim to cover 165 lineal feet. Use 6-7 Ground Spikes per channel.

*Panels taller than 48" require interior bracing. We recommend using steel "J" ground channel for bracing. *Decks require extra materials. For decks, add the lengths of the two sides running away from home to total lineal feet, and refer to chart. To cover a hitch, add 8 feet to total lineal feet. (1) steel ground channel and (1) steel corner piece are recommended for bracing and covering one hitch. For sturdier hitch covers, use wood bracing. *Lifetime Top Front trim can be combined with ground channel for added protection from weed trimmers. *Homes on inclines will use extra ground channel. Sloped walk ramps and sides of steps will use extra top trim.

Exterior Refurb

ROCK SKIRTING KITS

Box Size (LF) ▼	Rock Panel	10' Top Trim	10' Ground Channel	Rock Vent	Hex Screws	Ground Spikes
16 x 56 (144)	31	15	15	14	500	90
32 x 42 (148)	31	15	15	14	500	90
28 x 48 (152)	32	16	16	16	500	100
28 x 52 (160)	34	17	17	16	500	105
28 x 56 (168)	36	17	17	16	500	105
28 x 60 (176)	37	18	18	18	600	110
16 x 76 (184)	39	19	19	18	600	115
28 x 68 (192)	41	20	20	20	600	120
32 x 66 (196)	41	20	20	20	600	120
28 x 72 (200)	42	21	21	20	700	120
28 x 76 (208)	44	21	21	22	700	120
32 x 76 (216)	46	22	22	22	700	130

Helpful Notes:

Panel counts based on average heights of 32"- 48". See notes above regarding decks and hitches. *Actual panel width: 57.5" *48" x 60" panels can be turned on side to become 60" x 46.5". Panels taller than 48" require interior bracing. Determine average height with several measurements from ground to bottom of siding. 48" x 60" panels can be cut in half and used for average heights of 30" or less. Holes can be drilled into panel for extra ventilation. Chart does not include rock doors, which are 32" wide and can be used in lieu of 1/2 panel.

